

Focus

RTL34214 - Rounded - Adj / 4,5 W / 4000 K / CRI >80

DESCRIPTION

Small and performing, the Focus series of recessed minispots create precise accents of light without glare thanks to the backward position of the LED source. In the fixed and adjustable versions, the Focus minispots emit bright light within a sharp and smudge-free beam with only 4.5 W of electricity absorption. The LEDs selected from the first labels and the body entirely made of die-cast aluminum ensure both a long life to the LED source and the constancy of its colorimetric characteristics over time (L80 / B20 at 50,000 hours). Focus is available in a matt white and matt black finish and complete of wired driver.

www.panint.it



Switch

Firenze, Italy

On÷Off

PRODUCTS CHARACTERISTICS

| installation type | Recessed Spotlights | |
|------------------------------|---------------------|-----------|
| material | Aluminum | |
| Color | White | |
| Power | 4,5 W | 30° |
| Lumen output - Full emission | 220 lm | |
| Efficacy | 88 lm/W | 50 |
| Diameter | ø 52 mm. | |
| Dimensions | h 50 mm. | |
| net weight | 0,10 kg. | |
| | - | |
| | | ~~- |
| | | |
| | | 🕑 ø45 mm. |
| | | |
| | | ه] 0,10 |
| | | 0,10 |
| | | |
| | | |
| | | |

| ELECTRICAL CHARACTERISTICS | | | | | |
|---------------------------------------------------------------|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| driver | On÷Off | | | | |
| MECHANICAL CHARACTERISTICS | | | | | |
| product IP rate | IP20 | | | | |
| HOLE RECESS DIMENSIONS | | | | | |
| PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle | Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it | This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice. | | | |



Focus

RTL34214 - Rounded - Adj / 4,5 W / 4000 K / CRI >80

| hole recess diameter | ø 45 mm. |
|----------------------|----------|
|----------------------|----------|

LED SOURCE DETAILS

| RG 1 Low risk (IEC 62471) 700 mA |
|---------------------------------------|
| 700 mA |
| |
| 4000 K |
| CRI >80 |
| < 3 |
| |

DRIVER CHARACTERISTICS

| driver | On÷Off | |
|------------------------------|------------|--|
| | | |
| LIGHTING DETAILS | | |
| luminous effect | spot | |
| optic | 38° | |
| optic Beam angle - direct | 38° | |

PHOTOMETRIC

