

Focus

RTL34216 - Squared - Adj / 4,5 W / 4000 K / CRI >80

DESCRIPTION

Small and performing, the Focus series of recessed minispots create precise accents of light without glare thanks to the backward position of the LED source. In the fixed and adjustable versions, the Focus minispots emit bright light within a sharp and smudge-free beam with only 4.5 W of electricity absorption. The LEDs selected from the first labels and the body entirely made of die-cast aluminum ensure both a long life to the LED source and the constancy of its colorimetric characteristics over time (L80 / B20 at 50,000 hours). Focus is available in a matt white and matt black finish and complete of wired driver.

www.panint.it




Switch

Firenze, Italy

On÷Off

PRODUCTS CHARACTERISTICS

- installation type material Color Power Lumen output - Full emission Efficacy Dimensions net weight
- Recessed Spotlights Aluminum White 4,5 W 215 Im 86 Im/W 50 x 50 mm. 0,10 kg.



ELECTRICAL CHARACTERISTICS			
driver	On÷Off		
MECHANICAL CHARAC	TERISTICS		
product IP rate	IP20		
HOLE RECESS DIMENSI	ONS		
PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle	Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it	This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.	



Focus

RTL34216 - Squared - Adj / 4,5 W / 4000 K / CRI >80

hole recess diameter	ø 45 mm.	
LED SOURCE DETAILS		
led source type	Power Led	
Photobiological risk	RG 1 Low risk (IEC 62471)	
LED current	700 mA	
Light temperature	4000 K	
CRI	CRI >80	
SDCM	< 3	
DRIVER CHARACTERISTICS		
driver	On÷Off	
LIGHTING DETAILS		
luminous effect	spot	
optic	20°	
Beam angle - direct	20°	
ŭ		

PHOTOMETRIC

