

### **Focus**

RTL34217 - Squared - Adj / 4,5 W / 3000 K / CRI > 80

### **DESCRIPTION**

Small and performing, the Focus series of recessed minispots create precise accents of light without glare thanks to the backward position of the LED source. In the fixed and adjustable versions, the Focus minispots emit bright light within a sharp and smudge-free beam with only 4.5 W of electricity absorption. The LEDs selected from the first labels and the body entirely made of die-cast aluminum ensure both a long life to the LED source and the constancy of its colorimetric characteristics over time (L80 / B20 at 50,000 hours). Focus is available in a matt white and matt black finish and complete of wired driver.




Switch On÷Off

#### PRODUCTS CHARACTERISTICS

installation type
material
Color
Power
Lumen output - Full emission
Efficacy
Dimensions
net weight

Recessed Spotlights Aluminum White 4,5 W 200 Im 80 Im/W 50 x 50 mm.

0,10 kg.



## **ELECTRICAL CHARACTERISTICS**

driver On÷Off

# MECHANICAL CHARACTERISTICS

product IP rate IP20

### **HOLE RECESS DIMENSIONS**



# **Focus**

# RTL34217 - Squared - Adj / 4,5 W / 3000 K / CRI > 80

hole recess diameter ø 45 mm.

### LED SOURCE DETAILS

led source type Power Led

Photobiological risk RG 1 Low risk (IEC 62471)

LED current 700 mA
Light temperature 3000 K
CRI CRI >80
SDCM <3

## **DRIVER CHARACTERISTICS**

driver On÷Off

# LIGHTING DETAILS

luminous effect spot optic 38°
Beam angle – direct 38°

#### **PHOTOMETRIC**

