

Ska Base

RTL47207 - 25 W - 2400 lumen - 36° - Flood / 25 W / 4000 K / CRI > 92

DESCRIPTION

The SKA projectors are particularly suitable for the lighting of commercial environments such as shops and malls. The high lighting performance allows adequate illumination of the exhibition surfaces and exposed objects. The SKA projectors are equipped with selected drivers and CoB LEDs (prime brand) and the light color qualities (CRI > 90 and SDCM < 3) guarantee an excellent color rendering of the illuminated objects. The light emission is managed with high efficacy interchangeable optics to obtain maximum efficiency and maximum flexibility. Available On / Off version.



Switch

On:Off

PRODUCTS CHARACTERISTICS

installation type

Track / Ceiling projectors

material

Aluminum

Color

White

Power

25 W

Lumen output - Full emission

2450 lm

Efficacy


98 lm/W

Dimensions

82 x 192 mm.

net weight

0,85 kg.



ELECTRICAL CHARACTERISTICS

feeding

220÷240 V

driver

On:Off

Insulation class

Class I

MECHANICAL CHARACTERISTICS

product IP rate

IP20

Ska Base

RTL47207 - 25 W - 2400 lumen - 36° - Flood / 25 W / 4000 K / CRI > 92

LED SOURCE DETAILS

led source type	CoB Led
Photobiological risk	RG 1 Low risk (IEC 62471)
LED brand	Bridgelux or equivalent
LED current	600 mA
Service lifetime	L80 / B20 - 50.000 h.
Light temperature	4000 K
CRI	CRI > 92
SDCM	< 3

DRIVER CHARACTERISTICS

driver	On÷Off
Operating temperature	-20°C ÷ 45°C

LIGHTING DETAILS

luminous effect	flood
Beam angle - direct	36°
Cut Hood	32°

PHOTOMETRIC

