

Pill

RTL48102 - 2,5 W / 3000 K / CRI >80

DESCRIPTION

Adjustable recessed luminaire for indoor installation. Black anodized aluminum body and steel springs fixing system. Three secondary optics (lenses) and two colour temperature available. Thanks to small height and the small dimensions it is ideal for lighting of display cases and niches, as well as for installation in shelves and everywhere it's required reduced thickness.



PRODUCTS CHARACTERISTICS

installation type material	Recessed Spotlights Aluminum			
Finish Color Power Lumen output – Full emission Efficacy Diameter net weight	Anodized White 2,5 W 270 lm 90 lm/W ø 60 mm. 0,09 kg.		Ø53 90° Ø60	
		(I) ø56 mm		kg 0,09

ELECTRICAL CHARACTERISTICS

feeding Insulation class 700 mA CC Class III

MECHANICAL CHARACTERISTICS

product IP rate

IP40

PAN Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan Srl. All rights reserved. We reserve the right to make technical changes without notice.



Pill

RTL48102 - 2,5 W / 3000 K / CRI >80

hole recess diameter	ø 56 mm.	
LED SOURCE DETAILS		
led source type	Power Led	
Photobiological risk	RG 2 Moderate risk (IEC 62471)	
LED current	700 mA	
Light temperature	3000 K	
CRI	CRI >80	
LIGHTING DETAILS		

emission	rotationally symmetrical
luminous effect	flood
optic	25°
Beam angle - direct	25°

PHOTOMETRIC

