

Nemo TL Adj

RTT20110 - Trimless + Matt Reflector - 15 W - 1450 lumen / 4000 K / CRI >90

DESCRIPTION

Nemo TL is the trimless series of the Nemo family designed for installations in plasterboard false ceilings with no visible edge. Models up to 24W are equipped with a pre-drilled fixed frame for direct fixing of the luminaire to the false ceiling; The 33W and 42W models are equipped with height-adjustable fixing frame. Four beam openings with 38 $^{\circ}$ cut-off and versions up to UGR <17 allow to obtain the right balance between luminance control and light diffusion. The lighting modules are all equipped with latest generation LEDs with CRI> 90 and SDCM < 3. The range of Nemo TL Adj and Nemo TL Fix has interchangeable secondary reflectors available in five different aesthetic finishes that allow the system to be characterized even after the first installation. The safety cable supplied prevents accidental drops and the "fast plug" connection system to the driver allows quick and safe installation. Nemo ADJ version for accent lighting with 350 $^{\circ}$ adjustability on the horizontal plane and 30 $^{\circ}$ on the vertical plane. Nemo Fix is perfect for vertical lighting for the control of direct glare and soft light at the edges of the beam.




Switch

On÷Off

PRODUCTS CHARACTERISTICS

trimless recessed installation type material **Aluminum** Satin Color 15 W Power 1486 lm Lumen output - Full emission 99 lm/W Efficacy Ø 71 mm. Diameter **Dimensions** h 112 mm. net weight 0,36 kg.



ELECTRICAL CHARACTERISTICS

feeding 220÷240 V driver On÷Off





Nemo TL Adj

RTT20110 - Trimless + Matt Reflector - 15 W - 1450 lumen / 4000 K / CRI >90

Insulation class Class II

MECHANICAL CHARACTERISTICS

optical compartment IP rate IP40 recessed compartment IP rate IP20 IK IK02

HOLE RECESS DIMENSIONS

hole recess diameter Ø 76 mm.

LED SOURCE DETAILS

led source typeCoB LedLED brandBridgeluxLED current350 mALED voltage36 V

Service lifetime L80 / B20 - 50.000 h.

Light temperature 4000 K
CRI CRI >90
SDCM <3

DRIVER CHARACTERISTICS

driver On÷Off
Power factor > 0,9

LIGHTING DETAILS

emission rotationally symmetrical

luminous effectspotoptic 15° Beam angle - direct 15° UGR ≤ 17 Cut Hood 38°





Nemo TL Adj

RTT20110 - Trimless + Matt Reflector - 15 W - 1450 lumen / 4000 K / CRI >90

PHOTOMETRIC

