

Nemo TL Fix

RTT21543CA - Trimless + Matt White Reflector - 10 W - 920 lumen / 2700 K / CRI >90

DESCRIPTION

Nemo TL is the trimless series of the Nemo family designed for installations in plasterboard false ceilings with no visible edge. Models up to 24W are equipped with a pre-drilled fixed frame for direct fixing of the luminaire to the false ceiling; The 33W and 42W models are equipped with height-adjustable fixing frame. Four beam openings with 38 $^{\circ}$ cut-off and versions up to UGR <17 allow to obtain the right balance between luminance control and light diffusion. The lighting modules are all equipped with latest generation LEDs with CRI> 90 and SDCM <3. The range of Nemo TL Adj and Nemo TL Fix has interchangeable secondary reflectors available in five different aesthetic finishes that allow the system to be characterized even after the first installation. The safety cable supplied prevents accidental drops and the "fast plug" connection system to the driver allows quick and safe installation. Nemo ADJ version for accent lighting with 350 ° adjustability on the horizontal plane and 30 ° on the vertical plane. Nemo Fix is perfect for vertical lighting for the control of direct glare and soft light at the edges of the beam.




Switch

Casambi

PRODUCTS CHARACTERISTICS

installation type material Color Power Lumen output - Full emission Efficacy Diameter Dimensions net weight trimless recessed Aluminum Matt white 10 W 896 lm 90 lm/W Ø 71 mm. h 89 mm. 0,28 kg.



ELECTRICAL CHARACTERISTICS

feeding driver	220÷240 V Casambi	
PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle	Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it	This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.
Firenze, Italy	www.panint.it	Uploaded 31/03/21 - pg 1 / 3



Nemo TL Fix

RTT21543CA - Trimless + Matt White Reflector - 10 W - 920 lumen / 2700 K / CRI >90

Insulation class	Class II
MECHANICAL CHARACTERISTICS	
optical compartment IP rate recessed compartment IP rate IK	IP40 IP20 IK02
HOLE RECESS DIMENSIONS	
hole recess diameter	Ø 76 mm.

ENERGY CLASSIFICATION



LED SOURCE DETAILS

led source type	CoB Led
LED brand	Bridgelux
LED current	250 mA
LED voltage	36 V
Service lifetime	L80 / B20 - 50.000 h.
Light temperature	2700 K
CRI	CRI >90
SDCM	< 3

DRIVER CHARACTERISTICS

driver	Casambi
Power factor	> 0,5
Operating temperature	-20°C ÷ 45°C



Nemo TL Fix

RTT21543CA - Trimless + Matt White Reflector - 10 W - 920 lumen / 2700 K / CRI >90

LIGHTING DETAILS

emission	rotationally symmetrical
luminous effect	flood
optic	38°
Beam angle - direct	38°
UGR	≤ 19
Cut Hood	38°

PHOTOMETRIC

