

Nemo TL Comfort

RTT22427CA - Trimless + Matt Bronze Reflector - 33 W - 3100 lumen / 3000 K / CRI >90

DESCRIPTION

Nemo TL is the trimless series of the Nemo family designed for installations in plasterboard false ceilings with no visible edge. Models up to 24W are equipped with a pre-drilled fixed frame for direct fixing of the luminaire to the false ceiling; The 33W and 42W models are equipped with height-adjustable fixing frame. Nemo TL Comfort is the solution for installations with maximum visual comfort; thanks to its 48 ° cut off, the TL Comfort version of the Nemo series guarantees maximum control of direct glare. The lighting modules are all equipped with the latest generation of LEDs (CRI> 90 and SDCM <3). The interchangeable secondary reflectors are available in four different satin finishes and allow you to aesthetically characterize the system even after the first installation without changing the lighting performance. The safety cable supplied prevents accidental drops and the "fast plug" connection system to the driver allows quick and safe installation.



Switch

Casambi

PRODUCTS CHARACTERISTICS

installation type material Color Power Lumen output - Full emission Efficacy Diameter Dimensions net weight	trimless recessed Aluminum Matt bronze 33 W 3028 lm 92 lm/W Ø 121 mm. h 200 mm. 0,99 kg.	200 355° 355° № 0,99 № ø125 mm.
---	--	--

ELECTRICAL CHARACTERISTICS

feeding driver Insulation class 220÷240 V Casambi Class II

PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.




Nemo TL Comfort

RTT22427CA - Trimless + Matt Bronze Reflector - 33 W - 3100 lumen / 3000 K / CRI >90

optical compartment IP rate IP40 recessed compartment IP rate IP20 IK IK02 HOLE RECESS DIMENSIONS	recessed compartment IP rate IP20	
IK IK02		
	IK IK02	
HOLE RECESS DIMENSIONS		
	HOLE RECESS DIMENSIONS	
hole recess diameter Ø 125 mm.	hole recess diameter Ø 125 mm.	

ENERGY CLASSIFICATION



LED SOURCE DETAILS

led source type LED brand LED current LED voltage Service lifetime Light temperature CRI	CoB Led Bridgelux 800 mA 36 V L80 / B20 - 50.000 h. 3000 K CRI >90
SDCM	< 3

DRIVER CHARACTERISTICS

driver	Casambi
Power factor	> 0,9
Operating temperature	-20°C ÷ 45°C

LIGHTING DETAILS

emission

rotationally symmetrical

PAN International Srl Via G. Michelucci, 1 50028 Barberino Tavarnelle Firenze, Italy Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338 panint@panint.it www.panint.it

This datasheet is property of Pan International Srl. All rights reserved. We reserve the right to make technical changes without notice.



Nemo TL Comfort

RTT22427CA - Trimless + Matt Bronze Reflector - 33 W - 3100 lumen / 3000 K / CRI >90

luminous effect	flood
optic	24 °
Beam angle - direct	24 °
UGR	≤ 17
Cut Hood	48 °

PHOTOMETRIC

