

Datasheet

Color Quality

STP10040 - PCB size 10 mm. - 14,4 W/m - 80 LED/m - Cut 100 mm. / 2700 K / CRI > 95

DESCRIPTION

The Color Quality Stripled series is characterized by the high standard of color rendering. It is indicated for particular applications where perfect colors are required; the appreciation of the colors is guaranteed by the optimal mixing of the flow emitted by the individual emitters, without thus affecting the luminous efficacy which always remains at excellent levels. This combination makes the Color Quality Stripled the perfect choice for installations in shop windows, inside show rooms, or for museum applications.



PRODUCTS CHARACTERISTICS

installation type	Stripled	
Power	14,4 W/m	80 LED/m.
Lumen output – Full emission	1440 lm/m	
Efficacy	100 lm/W	
		100 mm
		A A

ELECTRICAL CHARACTERISTICS		
feeding Insulation class	24 V DC Class III	
MECHANICAL CHARAC	TERISTICS	
product IP rate	IP20	
PAN Srl Via G. Michelucci, 1	Tel. +39 055 80 59 336/7 Fax +39 055 80 59 338	This datasheet is property of Pan Srl. All rights reserved. We reserve the right to
50028 Barberino Tavarnelle Firenze, Italy	panint@panint.it www.panint.it	make technical changes without notice.



Color Quality

STP10040 - PCB size 10 mm. - 14,4 W/m - 80 LED/m - Cut 100 mm. / 2700 K / CRI > 95

LED SOURCE DETAILS

led source type Light temperature CRI SMD LED - 2835 2700 K CRI > 95